

Intimidator Spot 360X IP

- Outdoor-rated moving head designed for situations where mother nature gets in the way
- Power input/output connections save setup time while maintaining water resistance
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Durable magnesium housing is lightweight, strong and corrosion resistant
- Dual rotating prisms split the beam for great effects and cover a larger area
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Fits best in the Intimidator Road Case

Specifications

- DMX Channels: 8 or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (6 metal + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobo Size: 24 mm outside, 20 mm image, 0.5 mm max thickness
- Prism: 5-facet linear, bi-directional at variable speeds
- Prism: 3-facet round, bi-directional at variable speeds
- Light Source: 1 LED (cool white) 100 W, (4.3 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 15°
- Illuminance (2m): 23,978 lux
- Illuminance (5m): 3,836 lux
- Lumens: 4268
- Color Temperature: 15,000 K
- IP Rating: IP65
- Startup Temperature: -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature: -22 °F to 113 °F (-30 °C to 45 °C)
- Power Linking: 5 units @ 120 V; 9 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 190 W, 2.4 A @ 120 V, 60 Hz
- Power and Current: 185 W, 1.4 A @ 230 V, 50 Hz
- Bracket Mounting Hole: 13 mm
- Approvals: CE, MET, UKCA, ROHS



- Cable Length: 5 ft (1.5 m)
- Weight: 23 lb (10.4 kg)
- Size: 11.8 x 8.5 x 15.9 in (299 x 217 x 406 mm)
- Optional Controllers: RFC, RFC-XL

