

General Information		Application(s):	What's Included:
Product Name:	STRIKE Bolt 1C	<ul style="list-style-type: none"> • Concert / Touring • Other Rental / Production • Special Events • Television (Performance Shows) 	<ul style="list-style-type: none"> • Fixture • 1pc Power Cord • 1pc Omega Bracket • 1pc Stealth Filter
Product Type:	Static Strobe		
Replacement to:	N/A		
Target Dealer:	\$1,350.00		
Target MAP:	\$1,800.00		
Target List/MSRP:	\$2,030.00		
UPC Code:	781462223625		
Certifications:	CE (LV/EMC), UKCA, RoHS, MET,		

Key Features & Benefits:

- Intense, stackable strobe with added color effects rated IP65 for all-weather use
- Twin strobe tubes from the Color STRIKE M for intense strobe effects
- Single row of RGBA LEDs for color block effects behind an integrated smart glass (electronic frost) filter
- Designed for rigging versatility with multiple hanging points, end-to-end connections, floor feet, and the ability to be rigged inline with STRIKE Array fixtures to create unique blinder/strobe arrays.

Product Images



Why Product Was Developed:

Customers have largely adopted the popular Color STRIKE M unit, and have asked us to develop a simplified, static strobe option that features similar characteristics. STRIKE Bolt 1C does just that. The unit has similar strobe and colorchanging capabilities as the Color STRIKE M, as well as a dual inner tube, but pulls in a distinctly unique feature of the STRIKE Array family into the mix. Even though STRIKE Bolt 1C is not motorized, the unit has the same tool-less stacking system developed for the STRIKE Array family which allows it to become part of the configurations customers make with the STRIKE Array family. And for the first time ever in the STRIKE family, we've included an integrated Smart Glass feature to the STRIKE Bolt 1C for an epic, frosted eye-candy/wash effect.

Elevator Pitch

STRIKE Bolt 1C takes the power of the dual strobe tubes from the Color STRIKE M and puts them in a static fixture with the flexibility to be hung anywhere. Couple this with "smart glass" that instantly frosts the front lens creating a beautiful eye-candy/color block effect. The addition of a stealth filter can all but make the fixture disappear for on-camera use.

Product Positioning

IP65, twin tube static strobe with RGBA eye-candy behind smart glass for instant color block effects that can instantly shift to powerful strobe bursts. A multitude of rigging options creates a versatile, traditional looking strobe with modern flair. The unit is ideal for festivals, concert and touring, broadcast and the likes.

Product Comparison Matrix



Manufacturer	CHAUVET Professional	ROXX	GLP	Martin
Product Name	STRIKE Bolt 1C	Cluster S2	JDC Line 500	Atomic 3000 LED
Light Source	392 CW & 66 RGB 1.5W LEDs	612 CW & 680 RGB LEDs	100 CW & 200 RGB LEDs	64 RGB, 228 CW (10W)
LED Base Color Temp. (White Only)	5600K	Not Listed	6500K	5700K
Controllable Sections	28 CW, 2 RGB	12 x 4 CW, 6 x 2 RGB	"25mm"	1
Projected Lumens (Full on, Not Strobe)	20819	14807	48377	170511
Lux @ 5m	466 (1,480 in Strobe)	1,605 (in Strobe)	971	4042
CRI	92	88	78	Not Listed
Beam Angle / Field Angle	80° / 131°	66° / 108°	23° x 118° / 31° x 128°	66° / 81.5°
Zoom Range	None	None	None	None
Motorized Pan/Tilt Range	None	None	None	None
Cooling System / Modes	Fan	Fan	Fan	Fan
dBA/Full Intensity (1m)	Not Listed	Not Listed	Not Listed	Not Listed
Color Mixing	RGBW	RGBW	RGB	RGB Backlight
Color Temperature Range	2,700 - 10,000K	2,000-10,000K	2,500 - 10,000K	Not Listed
+/- Green Adjustment	No	No	No	No
Emulated Red Shift	No	No	No	No
Variable PWM	Yes	Yes	Yes, But Limited Options	No
IP Rating	IP65	IP65	IP20	IP20
Data Protocol(s)	DMX, RDM	DMX, RDM, Art-Net, sACN	DMX, RDM	DMX, RDM
Data Connection	5-pin DMX	5-pin DMX, RJ45	5-pin DMX	5-pin DMX
Power Connection	TRUE1	True1	True1	TRUE1 In
Input Voltage	100-240v	100-240v	100-240v	100-240v
Size	15 x 8.4 x 11.8in 380 x 213 x 300mm	15.75 x 7.87 x 7.52in 400 x 200 x 191mm	20 x 7.9 x 2.9in 507 x 201.5 x 74mm	16.8 x 9.7 x 9.5 in 425 x 245 x 240mm
Weight	25.1lb / 11.4kg	27.8lb / 12.6kg	13.23lb / 6kg	17.2lb / 7.8kg
Fixture Interlock/Alignment	STRIKE Array and Integrated	Coffin Locks with B2/4 Series	Proprietary Brackets	No
Accessory Slot	No	Magnetic (optional filters)	Yes	Optional Filter Holder, Atomic Colors
Warranty	3-years	2-years	2-years	2-years

Product Comparison Matrix



Manufacturer	CHAUVET Professional	Elation	Solaris
Product Name	STRIKE Bolt 1C	Protron Eclipse	Flare Q+
Light Source	392 CW & 66 RGB 1.5W LEDs	96, 10W, RGBW LEDs	96, 10W, RGBW LEDs
LED Base Color Temp. (White Only)	5600K	N/A	N/A
Controllable Sections	16 CW, 2 RGBA	12	12
Projected Lumens (Full on, Not Strobe)	20819	26,654 (Unstable), 22,627 (Stable)	34440
Lux @ 5m	466 (1,480 in Strobe)	3,082 (Unstable), 2,645 (Stable)	3026
CRI	92	Not Listed	Not Listed
Beam Angle / Field Angle	80° / 131°	31° / 59°	35° / 68°
Zoom Range	None	None	None
Motorized Pan/Tilt Range	None	None	None
Cooling System / Modes	Fan	Fan	Fan
dB(A)/Full Intensity (1m)	Not Listed	Not Listed, But has Silent Mode	Not Listed, But has Silent Mode
Color Mixing	RGBW	RGBW	RGBW
Color Temperature Range	2,700 - 10,000K	2,700 - 10,000K	Not Listed
+/- Green Adjustment	No	No	No
Emulated Red Shift	No	No	No
Variable PWM	Yes	No	No
IP Rating	IP65	IPX4	IP20
Data Protocol(s)	DMX, RDM	DMX, RDM, Kling-Net, Art-Net	DMX, RDM
Data Connection	5-pin DMX	5-pin DMX, RJ45	5-pin DMX
Power Connection	TRUE1	TRUE1 In and Thru	powerCON In and Thru
Input Voltage	100-240v	100-240v	100-277v
Size	15 x 8.4 x 11.8in 380 x 213 x 300mm	24.9 x 14.4 x 7in 633 x 364.8 x 177.5mm	10 x 19.7 x 6.5in 257 x 500 x 164mm
Weight	25.1lb / 11.4kg	34.6lb / 15.7kg	22lb / 10kg
Fixture Interlock/Alignment	STRIKE Array and Integrated	Interlocking	No
Accessory Slot	No	No	Optional Filter Holder
Warranty	3-years	2-years	2-years

