

General Information		Application(s):	What's Included:
Product Name:	Strike Array 2C	<ul style="list-style-type: none"> • Concert / Touring • Other Rental / Production • Special Events • Television (Performance Shows) 	<ul style="list-style-type: none"> • Power Cord • Omega Bracket
Product Type:	IP65 Color Blinder		
Replacement to:	N/A		
Target Dealer:	\$1,312.50		
Target MAP:	\$1,750.00		
Target List/MSRP:	\$1,979.99		
UPC Code:	781462224141		
Certifications:	CE, UKCA, MET, FCC		

Key Features & Benefits:

- Intense 2 pod color blinder/strobe rated IP65 for all-weather use
- Full range of color and excellent rendition of any color temperature of white
- Emulated “red shift” to mimic incandescent fixtures perfectly.
- Individual pan (or tilt depending on mount orientation) of each head to allow for directional adjustment of light output.
- Innovative interlocking system to connect multiple Strike Array family fixtures together.
- Multiple mounting locations and repositionable yoke with ¼ turn adaptors for creative and convenient rigging options
- Independent pod control and strobe functionality for high-impact effects on the fly

Product Images



Why Product Was Developed:

There is a need in the market for high-power IP65-rated blinders that serve the dual purpose of producing stunning, and unexpected eye-candy visuals. STRIKE Array 2C brings color-infused capabilities to the popular Strike Array 2, offering users a fixture that can be used as a traditional blinder with high quality white light, but has the added versatility of achieving any mood with full color control of each pod. The units' feature the same interlocking system developed for other Strike Array units.

Elevator Pitch

Building off the success and benchmark setting standards of the Strike Array series the Strike Array 2C provides all the benefits of the original fixture but adds an LED array capable of achieving powerful saturated colors in addition to any color temperature of white in one fixture.

Product Positioning

IP65, full color blinder with benchmark setting dimming that can work alongside all the other fixtures in the Strike Array family makes these units ideal for rental houses, festivals, concert and touring and the likes.

Product Comparison Matrix

					
Manufacturer	CHAUVET Professional	ROXX	CHAUVET Professional	ROXX	Elation
Product Name	Strike Array 2C	Cluster B2 FC	Strike Array 2	Cluster B2 W	DTW Blinder 350 IP
Light Source	2, 250W RGBAwW Arrays	2, 260W RGBAwW	2, 100W WW with Amber	2, 300W WW with Amber + Red	2, 175W WW/Amber COB
LED Base Color Temp. (White Only)	N/A	N/A	3100K	2900K	3100K
Projected Lumens	27021	16215	9698	Up to 20,000 (claimed)	5997
Lux @ 5m	1102	721	341	870	213
CRI	95	90	93	80	92.7
Beam Angle / Field Angle	57.1° / 97.2°	50° / 87°	61° / 100°	50° / 87°	64.6° / 96.8°
Zoom Range	N/A	N/A	N/A	N/A	N/A
Cooling System / Modes	Fan, w/modes	Fan, temperature regulated	Convection	Fan, temperature regulated	Convection
dBA/Full Intensity (1m)	TBD	Not Listed	0	Not Listed	0
Color Mixing	RGBAwW	RGBAwW	Emulated Red Shift	Emulated Red Shift	Emulated Red Shift
Color Temperature Range	2800 - 6500K	2000 - 10000K	1800-3200K	Not Listed	1800-3200K
+/- Green Adjustment	No	No	No	No	No
Emulated Red Shift	Yes	Yes	Yes	Yes	Yes
Variable PWM	Yes	Yes	Yes	Yes	No, "Flicker Free"
IP Rating	IP65	IP65	IP65	IP65	IP65
Data Protocol(s)	DMX, RDM	DMX, RDM	DMX, RDM	DMX, RDM	DMX, RDM
Data Connection	IP 5-pin XLR Panel Mount	IP 5-pin XLR Panel Mount	IP 5-pin XLR Panel Mount	IP 5-pin XLR Panel Mount	IP Whips to 5-pin
Power Connection	True1 Compatible	True1 Compatible	True1	True1 Compatible	True1
Input Voltage	100-240V Auto-Ranging	100-240V Auto-Ranging	100-240V Auto-Ranging	100-240V Auto-Ranging	100-240V Auto-Ranging
Size	19.1x7.5x10.4in 486x189.3x263.5mm	15.75x7.87x7.52in 400x200x191mm	18.5x10.4x6.3in 469x264.5x161mm	19.69x11.55x7.52in 500x293.5x191mm	15.7x9.5x9.6in 400x241x245mm
Weight	20.6lb / 9.4kg	23 lb / 10.5kg	17.6lb / 8kg	23.15lbs / 10.5kg	18lb / 8.2kg
Accessory Holder Size	N/A	N/A	N/A	N/A	N/A
Warranty	2-years	Not Listed	2-years	Not Listed	2-Years
Additional Lenses	No	No.	No	No	Yes, Narrow Beam Micro-Fresnel
Interlockable / Stackable	Yes, Top and Side Quick Lock with 2 and 4 Cell	Yes, Coffin Lock, magnetic pre-hang, Top & Side	Yes, Top and Side Quick Lock with 2 and 4 Cell	Yes, Coffin Lock, magnetic pre-hang, Top & Side	Yes, Side and top bolt together with 2 or 4 cell versions
Multiple Mounting Orientations	Yes	YES	Yes	YES	No
Approvals	CE, MET, UKCA	CE, UKCA	CE, MET	CE, UKCA	CE, ETL
Other Notes			WARM WHITE	WARM WHITE	WARM WHITE

